


## LARISA-RZ-PIN

~25° diffused beam and holder with location pins


### TECHNICAL SPECIFICATIONS:

Dimensions	9.9 +9.9 mm
Height	7.5 mm
Fastening	glue, pin
Colour	black
Box size	254 x 298 x 241 mm
Box weight	7.1 kg
Quantity in Box	10000 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
LARISA-RZ	Lens	PMMA	clear
LARISA-HOLDER-PIN	Holder	PC	black





#### PHOTOMETRIC DATA (MEASURED):




LED XQ-E  
 FWHM 24.0°  
 Efficiency 77 %  
 Peak intensity 2.600 cd/lm  
 Required components:




LED LUXEON C  
 FWHM 26.0°  
 Efficiency 73 %  
 Peak intensity 2.600 cd/lm  
 Required components:






LED LUXEON Z ES  
 FWHM 26.0°  
 Efficiency 71 %  
 Peak intensity 1.930 cd/lm  
 Required components:



LED NCSxE17A  
 FWHM 26.0°  
 Efficiency 60 %  
 Peak intensity 1.800 cd/lm  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):

<p></p> <p>LED NVSxE21A FWHM 28.0° Efficiency 60 % Peak intensity 1.500 cd/lm Required components:</p>		
<p> Opto Semiconductors</p> <p>LED Duris S5 (2 chip) FWHM 32.0° Efficiency 72 % Peak intensity 1.600 cd/lm Required components:</p>		

#### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)